



SUNOCO FLEET SAE 20W-50 CH-4 ENGINE OIL

OVERVIEW

SUNOCO FLEET SAE 20W-50 CH-4 ENGINE OIL is designed to meet the lubrication requirements of a variety of older diesel and gasoline fueled engines or vehicles operating in warmer climates. This oil can be used wherever API CH-4 or SJ lubricant is recommended or where a thicker film strength lubricant is desired. **SUNOCO FLEET SAE 20W-50 CH-4 ENGINE OIL** is specially formulated to provide superior protection, resist oxidation and provide the higher viscosity needed in climates where temperature ranges are above 50 degrees year-round.

FEATURES & BENEFITS

SUNOCO FLEET SAE 20W-50 CH-4 ENGINE OIL prevents sludge and varnish deposit build up on engine pistons, has good anti-foaming characteristics and excellent shear stability for lasting component protection. Its superior composition resists thermal and oxidation breakdown due to high temperatures and protects against wear and corrosion at the highest levels.

APPLICATIONS

SUNOCO FLEET SAE 20W-50 CH-4 ENGINE OIL can be used where any car, light duty truck, or heavy-duty diesel vehicles require a higher viscosity fluid to protect engine parts from high temperature conditions or heavy-duty service. It is also designed for applications where engines operate under extreme applications such as towing heavy equipment at high speeds over long distances.

SPECIFICATIONS

API CH-4/SJ

TYPICAL PROPERTIES

Product Code	5173
SAE Viscosity Grade	20W-50
Viscosity Index	127
Viscosity, cSt @ 100 °C	19.2
Viscosity, cSt @ 40 °C	172
Viscosity, cP @ -20°C	6500
Pour Point, °C(°F), max.	-26 (-15)
Flash Point (COC), °C (°F), min.	245 (473)
Zinc, wt.%	.107
Phosphorous, wt.%	.097
Sulfated Ash, wt.%	.323
TBN	9.0

Philadelphia, PA • orders@sunocolubes.com • www.sunocolubes.com • Tel:(800) 660-0761 • Fax:(215) 352-0140