



SUNOCO SUPER M ELITE PRO MOTORCYCLE OILS

OVERVIEW

SUNOCO SUPER M ELITE PRO MOTORCYCLE OILS are racing oils that have been intentionally designed for street use. These all synthetic, top-tier race lubricants are street legal and comply with statutory and regulatory requirements in all 50 states. Featuring an ultra-shear stable polymer backbone and a race-proven, technologically superior dispersant/inhibitor, **SUNOCO SUPER M ELITE PRO MOTORCYCLE OILS** also feature specialty detergents, antioxidants, and the best full synthetic base oils. These products are built to perform better, to protect better and to last better than typical motorcycle racing lubricants.

APPLICATIONS

SUNOCO SUPER M ELITE PRO MOTORCYCLE OILS racing lubricants are formulated for pro-level riders both on and off the track. Their street-legal system provides race-level heat, wear, and clutch protection for the most aggressive racing styles. **SUNOCO SUPER M ELITE PRO MOTORCYCLE OILS** can be used with turbo injectors and other forced air systems and are designed for use with direct gas injectors. These lubricants offer ultra-premium level protection for track bikes, gasoline drag bikes, track-days bikes, cruisers, sporters, race replicas, adventurer bikes, motocross bikes, flat track bikes, or any other multi-wheeled, motorcycle-driven machine where quality, protection, and longevity are paramount.

FEATURES & BENEFITS

SUNOCO SUPER M ELITE PRO MOTORCYCLE OILS offer unparallel wear protection, engine cleanliness, and long lubricant life in a product meant for racing but suitable for everyday riding. Specifically made for track bikes, **SUNOCO SUPER M ELITE PRO MOTORCYCLE OILS** are true-blue race lubricants. Offering a finely-tuned frictional profile expressly designed for wet-packed clutches under high stress operation with “feather” or shiftless use. Building on the exceptional varnish, sludge, and viscosity control of all the **SUNOCO SUPER M** lubricants, **SUNOCO SUPER M ELITE PRO MOTORCYCLE OILS** ratchets up the high temperature handling capabilities and cuts evaporative losses by as much as 6 times that of the **SUPER M GOLD** series of oils.

SPECIFICATIONS

API SN PLUS • JASO MA/MA2

TYPICAL PROPERTIES

Product Code	64913	99413
SAE Viscosity	10W-40	15W-50
Viscosity, cSt @ 100°C	15.8	18.1
Viscosity, cSt @ 40°C	99.8	130.5
Viscosity, CCS, cP @ °C	4,700 (-25)	5,100 (-20)
Viscosity Index	170	154
HT/HS, Cp @150°C	3.9	4.9
Calcium (%)	0.111	0.111
Phosphorous, Wt. (%)	0.084	0.084
Zinc, Wt. (%)	0.092	0.092
NOACK	3.2	1.8

Philadelphia, PA • orders@sunocolubes.com • www.sunocolubes.com • Tel:(800) 660-0761 • Fax:(215) 352-0140