



SUNOCO AMBER SEMI-FLUID GREASES

OVERVIEW

SUNOCO are versatile, general-purpose greases recommended for use in applications where operating temperatures are between 30 ° and 250° F, loads are less severe, and a semi-fluid product is required. **SUNOCO AMBER SEMI-FLUID GREASES** are extreme pressure, multipurpose, lithium greases developed for use in a wide variety of industrial and automotive applications where fluidic properties are desired.

APPLICATIONS

SUNOCO AMBER SEMI-FLUID GREASES are designed for use in a variety of industrial equipment, including centrifugal pumps, fans, compressor plain and roller bearings and offer outstanding performance in central lube systems, gearboxes, and many applications.

FEATURES & BENEFITS

SUNOCO AMBER SEMI-FLUID GREASES are manufactured with high-quality base oils, lithium 12-hydroxystearate soap thickener, extreme-pressure and anti-wear additives, as well as R&O inhibiting agents. They have good load-carrying capacity for wear protection, good oxidation resistance and protects against rust and corrosion. They are shear and thermally stable and are especially suitable for use in centralized lube systems.

SPECIFICATIONS

NLGI #0-000

TYPICAL PROPERTIES

Product Code	9413	9423	9473
NLGI Consistency	#0	#00	#000
Viscosity, 40°C, cSt	150-170	150-170	150-170
Viscosity, 100°C, cSt	15.6	15.6	15.6
Viscosity Index	95 min.	80 min.	80 min.
Penetration, 60 Strokes	355-385	400-430	445-475
Dropping Point, min.	330 min.	n/a	n/a
Oil Separation, % loss	Semi-Fluid	Semi-Fluid	Semi-Fluid
Copper Strip Corrosion, 210°F 3 hrs.	1b	1b	1b
Oxidation Stability, 100 hrs., psi loss	5	-	-
Timken OK Load	40 lbs.	40 lbs.	40 lbs
Rust Prevention	Pass	Pass	Pass