



SUNOCO BRF-30 BREAK-IN ENGINE OIL

OVERVIEW

SUNOCO BRF-30 BREAK-IN ENGINE OIL is a specially formulated mineral oil designed for exceptional protection and superior engine component wear-in. Its carefully balanced system of base oils and performance additives enables proper ring seating while ensuring the critical lubrication needs of cam shafts, lifters and rocker arms are met during the first 1,000 miles of engine use.

FEATURES & BENEFITS

SUNOCO BRF-30 BREAK-IN ENGINE OIL protects against excessive and undue wear and has been engineered for high performance engines operating in competitive environments. Anti-wear additives with high levels of zinc and phosphorus are utilized without the need for added friction modifiers that can inhibit proper part seating. **SUNOCO BRF-30 BREAK-IN ENGINE OIL** is a chemically advanced formula that provides thermal and oxidative stability, required detergency for the break in period, and the balanced protection to ensure long engine life.

APPLICATIONS

SUNOCO BRF-30 BREAK-IN ENGINE OIL is designed specifically for high-output, high horsepower engines, but can be used in any gasoline powered engine for off-road/racing run-in and break-in purposes. It provides protection for full power dyno runs and the first 1,000 track miles.

TYPICAL PROPERTIES

Product Code	BR30W
SAE Viscosity	30
Viscosity, cSt @ 100°C	12.0
Viscosity, cSt @ 40°C	104.1
Viscosity Index	105
Calcium, ppm	1300
Zinc, ppm	1825
Phosphorus, ppm	1650
Sulfur, ppm	1860
Nitrogen, ppm	1380
Magnesium, ppm	570