



## SUNOCO FULL SYN DEXRON®-VI/MERCON® LV ATF

### OVERVIEW

SUNOCO FULL SYN DEXRON®-VI/MERCON® LV ATF is a specifically engineered, fully synthetic, next generation low viscosity multi-vehicle ATF that is OEM licensed and approved against both GM DEXRON®-VI/MERCON® LV ATF specifications. This technologically advanced formulation provides optimum protection under the harshest driving conditions while providing maximum fuel efficiency and performance.

### FEATURES & BENEFITS

SUNOCO FULL SYN DEXRON®-VI/MERCON® LV ATF has excellent shear and oxidation stability, low foaming tendencies, exceptional wear resistance, and corrosion and pitting protection.

### TYPICAL PROPERTIES

Product Code	5163
Viscosity, cSt @ 100°C	5.98
Viscosity, cSt @ 40°C	29.8
Density, @ 15°C	.844
Flash, COC °C	152
Pour Point, °C	-50
Viscosity, cP @ -40°C	11,500
Phosphorous, %/wt.	.0194

### APPLICATIONS

Suitable for use against a wide range of ATF specifications\*, SUNOCO FULL SYN DEXRON®-VI/MERCON® LV ATF is also backwards compatible for use in older GM vehicles that specify Dexron III-H, Dexron III-G, Dexron II-D, Dexron II or Dexron fluids. This fluid is approved by General Motors under license number J-60439 and by Ford under license number MLV121216.

\*Not to be used for DCT or CVT applications. MERCON® V and SP not supported.

### SPECIFICATIONS

DEXRON® VI license #J-60439  
MERCON® LV license #MLV121216